# NSN 5315-00-934-0212

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-934-0212

## Head Diameter:

Between 0.310 inches and 0.530 inches

#### Shank Diameter:

Between 0.2470 inches and 0.2485 inches

## **Ring Handle Diameter:**

1.060 inches

#### **Detent Quantity:**

2

## **Actuation Method:**

Push button

Grip Length:

Between 0.500 inches and 0.520 inches

## Actuation Type:

Push

#### Hardness Rating:

40.0 rockwell c spindle

#### Shear Strength:

9200 double pound

## Shoulder To Head End Distance:

0.780 inches

## Pin Attachment Type:

Hook or ring

## Detent To Tapered End Distance:

Between 0.260 inches and 0.290 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

## **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

## Surface Treatment:

Passivate spindle

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

## Style Designator:

Ring handle

Shelf Life:

N/a

# Unit Of Measure:

---

#### **Demilitarization:**

No

Fiig:

A212a0