NSN 5315-00-936-0376

Headless Straight Pin - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5315-00-936-0376

First End Style:ChamferedPinlength:Between 0.365 inches and 0.370 inchesPindiameter:Between 0.1247 inches and 0.1249 inchesFirst End Taper Length:Between 0.010 inches and 0.020 inchesSecond End Relationship With First End:IdenticalHardness Rating:35.0 rockwell c and 45.0 rockwell cFirst End Taper Angle:Between 10.0 degrees and 20.0 degreesMaterial:Steel comp 410Material Specification:Ams 5613 assn standard single material responseSurface Treatment:PassivateShelf Life:N/a
Pinlength:Between 0.365 inches and 0.370 inchesPindiameter:Between 0.1247 inches and 0.1249 inchesFirst End Taper Length:Between 0.010 inches and 0.020 inchesSecond End Relationship With First End:IdenticalHardness Rating:35.0 rockwell c and 45.0 rockwell cFirst End Taper Angle:Between 10.0 degrees and 20.0 degreesMaterial:Steel comp 410Material Specification:Ams 5613 assn standard single material responseSurface Treatment:PassivateShelf Life:
Between 0.365 inches and 0.370 inches Pindiameter: Between 0.1247 inches and 0.1249 inches First End Taper Length: Between 0.010 inches and 0.020 inches Second End Relationship With First End: Identical Hardness Rating: 35.0 rockwell c and 45.0 rockwell c First End Taper Angle: Between 10.0 degrees and 20.0 degrees Material: Steel comp 410 Material Specification: Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
Pindiameter:Between 0.1247 inches and 0.1249 inchesFirst End Taper Length:Between 0.010 inches and 0.020 inchesSecond End Relationship With First End:IdenticalHardness Rating:35.0 rockwell c and 45.0 rockwell cFirst End Taper Angle:Between 10.0 degrees and 20.0 degreesMaterial:Steel comp 410Material Specification:Ams 5613 assn standard single material responseSurface Treatment:PassivateShelf Life:
Between 0.1247 inches and 0.1249 inches First End Taper Length: Between 0.010 inches and 0.020 inches Second End Relationship With First End: Identical Hardness Rating: 35.0 rockwell c and 45.0 rockwell c First End Taper Angle: Between 10.0 degrees and 20.0 degrees Material: Steel comp 410 Material Specification: Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
First End Taper Length:Between 0.010 inches and 0.020 inchesSecond End Relationship With First End:IdenticalHardness Rating:35.0 rockwell c and 45.0 rockwell cFirst End Taper Angle:Between 10.0 degrees and 20.0 degreesMaterial:Steel comp 410Material Specification:Ams 5613 assn standard single material responseSurface Treatment:PassivateShelf Life:
Between 0.010 inches and 0.020 inches Second End Relationship With First End: Identical Hardness Rating: 35.0 rockwell c and 45.0 rockwell c First End Taper Angle: Between 10.0 degrees and 20.0 degrees Material: Steel comp 410 Material Specification: Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
Second End Relationship With First End: Identical Hardness Rating: 35.0 rockwell c and 45.0 rockwell c First End Taper Angle: Between 10.0 degrees and 20.0 degrees Material: Steel comp 410 Material Specification: Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
Identical Hardness Rating: 35.0 rockwell c and 45.0 rockwell c First End Taper Angle: Between 10.0 degrees and 20.0 degrees Material: Steel comp 410 Material Specification: Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
Hardness Rating: 35.0 rockwell c and 45.0 rockwell c First End Taper Angle: Between 10.0 degrees and 20.0 degrees Material: Steel comp 410 Material Specification: Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
35.0 rockwell c and 45.0 rockwell c First End Taper Angle: Between 10.0 degrees and 20.0 degrees Material: Steel comp 410 Material Specification: Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
First End Taper Angle: Between 10.0 degrees and 20.0 degrees Material: Steel comp 410 Material Specification: Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
Between 10.0 degrees and 20.0 degrees Material: Steel comp 410 Material Specification: Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
Material: Steel comp 410 Material Specification: Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
Steel comp 410 Material Specification: Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
Material Specification: Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
Ams 5613 assn standard single material response Surface Treatment: Passivate Shelf Life:
Surface Treatment: Passivate Shelf Life:
Passivate Shelf Life:
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0