

View Online at <https://aerobasegroup.com/nsn/5315-00-937-0965>

**Shank Diameter:**

Between 0.3720 inches and 0.3735 inches

**Button Handle Diameter:**

Between 0.875 inches and 1.135 inches

**Detent Quantity:**

2

**End Application:**

W/s: ah-64-d longbow; missile, all-weather antiship, harpoon (agm-84); helicopter, mh-53e; engine, aircraft, f100-pw-200 (f-16a/b/c/d); lav, anti-tank; missile, minuteman lgm-30; boat, bridge erection, uscsbmk2; field artillery ammunition support vehicle (faagv)(m992); navstar global positioning system user equipment (ue); engine, aircraft f100-pw-229 (f15e, f16c/d)

**Grip Length:**

Between 1.500 inches and 1.520 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c

**Shoulder To Head End Distance:**

1.040 inches

**Pin Attachment Type:**

Hook

**Detent To Tapered End Distance:**

Between 0.335 inches and 0.365 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0