

View Online at <https://aerobasegroup.com/nsn/5315-00-937-0965>

Shank Diameter:

Between 0.3720 inches and 0.3735 inches

Button Handle Diameter:

Between 0.875 inches and 1.135 inches

Detent Quantity:

2

End Application:

W/s: ah-64-d longbow; missile, all-weather antiship, harpoon (agm-84); helicopter, mh-53e; engine, aircraft, f100-pw-200 (f-16a/b/c/d); lav, anti-tank; missile, minuteman lgm-30; boat, bridge erection, uscsbmk2; field artillery ammunition support vehicle (faagv)(m992); navstar global positioning system user equipment (ue); engine, aircraft f100-pw-229 (f15e, f16c/d)

Grip Length:

Between 1.500 inches and 1.520 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c

Shoulder To Head End Distance:

1.040 inches

Pin Attachment Type:

Hook

Detent To Tapered End Distance:

Between 0.335 inches and 0.365 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0