# NSN 5315-00-941-3605

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-941-3605

### Head Diameter:

Between 0.390 inches and 0.505 inches

## Shank Diameter:

Between 0.3095 inches and 0.3110 inches

# **Detent Quantity:**

2

#### **Actuation Method:**

Push button

#### Grip Length:

Between 0.600 inches and 0.620 inches

#### **Actuation Type:**

Pull and push

#### Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

#### Shear Strength:

## 12800 double pounds per square inch

Shoulder To Head End Distance:

1.030 inches

## Pin Center To Handle End Distance:

Between 1.200 inches and 1.300 inches

## Pin Attachment Type:

Link or ring

## Detent To Tapered End Distance:

Between 0.390 inches and 0.440 inches

Material:

Steel spring

## Material Specification:

Qq-w-470 federal specification single material response spring

## Surface Treatment:

Passivate handle

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response handle

## Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

# NSN 5315-00-941-3605

Quick Release Pin - Page 2 of 2

# Mil-std (military Standard):

Mil-s-6758 spec.

