

View Online at <https://aerobasegroup.com/nsn/5315-00-941-3755>

First End Style:

Chamfered

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.535 inches

Shank Length:

0.795 inches

Shoulder Width Across Flats:

0.750 inches

Shank Diameter:

Between 0.371 inches and 0.374 inches

Overall Length:

1.500 inches

First End Taper Length:

0.060 inches

Features Provided:

Casehardened

Second End Relationship With First End:

Identical

Thread Size:

0.375 inches

Second Shank Diameter:

0.375 inches

First End Location:

Both ends

First End Taper Angle:

45.0 degrees

Second Shank Length:

0.625 inches

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 cond f4 military specification single material response

Surface Treatment:

Chromium

Surface Treatment Specification:

Lac 0496 type 2 fscm 92887 mfr ref single treatment response or lac 0491 cl 1 fscm 98897 mfr ref single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.