NSN 5315-00-943-2054

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-943-2054 **Shank Diameter:** Between 0.4970 inches and 0.4985 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 1.300 inches and 1.320 inches **Actuation Type:** Push Hardness Rating: 40.0 rockwell c spindle **Shear Strength:** 36800 double pounds per square inch **Shoulder To Head End Distance:** 1.600 inches Pin Center To Handle End Distance: 1.860 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** Between 0.430 inches and 0.460 inches **Special Features:** Steel attaching hook or ring qq-w-423, comp 302, form 1, cond a, with passivated surface qq-p-35 Material: Steel comp 631 spring or steel comp 302 spring **Material Specification:** Qq-s-763 federal specification single material response detent **Surface Treatment:** Passivate spring **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spring **Style Designator:** L handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A212a0

NSN 5315-00-943-2054

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.