## NSN 5315-00-945-0547

Quick Release Pin - Page 1 of 1

**Fiig:** A212a0



View Online at https://aerobasegroup.com/nsn/5315-00-945-0547 **Shank Diameter:** Between 0.3095 inches and 0.3110 inches **Detent Quantity:** 2 **Actuation Method:** Push button **End Application:** Oaircraft, thunderbolt ii, a-10; support equipment, t-38 aircraft; aircraft, eagle f-15; support equipment, f-4 aircraft; support equipment, f-16 aircraftsupport equipment, t-37 aircraft; support equipment, f-15 aircraft **Grip Length:** Between 1.100 inches and 1.120 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c spindle **Shoulder To Head End Distance:** 1.270 inches Pin Center To Handle End Distance: 1.460 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** Between 0.300 inches and 0.330 inches Material: Steel comp 630 spindle or steel comp 632 spindle **Material Specification:** Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle **Surface Treatment:** Passivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spindle **Style Designator:** L handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** No