

View Online at <https://aerobasegroup.com/nsn/5315-00-945-0551>

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

Aircraft, eagle f-15; guided missile, intercept; helicopter, mh-53e; truck, fire/crash p15; f-22 raptor air dominance fighter; joint stars target radar sy stem; tank, abrams m-1; fms - a7 aircraft; aircraft, hercules c-130; aircraft,

Grip Length:

Between 1.000 inches and 1.020 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

1.270 inches

Pin Center To Handle End Distance:

1.460 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.260 inches and 0.290 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0