

View Online at <https://aerobasegroup.com/nsn/5315-00-945-0551>

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

Aircraft, eagle f-15; guided missile, intercept; helicopter, mh-53e; truck, fire/crash p15; f-22 raptor air dominance fighter; joint stars target radar sy stem; tank, abrams m-1; fms - a7 aircraft; aircraft, hercules c-130; aircraft,

**Grip Length:**

Between 1.000 inches and 1.020 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

1.270 inches

**Pin Center To Handle End Distance:**

1.460 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

Between 0.260 inches and 0.290 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0