

View Online at <https://aerobasegroup.com/nsn/5315-00-949-1894>

Head Diameter:

Between 0.510 inches and 0.630 inches

Shank Diameter:

Between 0.3720 inches and 0.3735 inches

Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

Aw/s: aircraft, tomcat f-14; tacsatcom, an/tsc-85 and an/tsc-93; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); aircraft, hercules c-130; ship, ohio class ssn (trident); helicopter, seasprite h-2

Grip Length:

Between 1.000 inches and 1.020 inches

Actuation Type:

Pull and push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

1.000 inches

Pin Attachment Type:

Hook

Detent To Tapered End Distance:

Between 0.460 inches and 0.510 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0