## NSN 5315-00-949-9064

Headed Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-949-9064

Head St	yle:	
---------	------	--

Pan no. 2 (r1 not required in item description)

## **Chamfer Length:**

Between 0.020 inches and 0.030 inches

Diameter:

Between 0.156 inches and 0.157 inches

**Under Head Length:** 

Between 0.645 inches and 0.655 inches

**Hole Arrangement Style:** 

One end drilled

First Hole Diameter:

Between 0.061 inches and 0.065 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.100 inches and 0.120 inches

**Features Provided:** 

Casehardened

**Hardness Rating:** 

52.0 rockwell c and 56.0 rockwell c

Pin Chamfer Angle:

Between 43.0 degrees and 47.0 degrees

**Pin Head Diameter:** 

Between 0.300 inches and 0.320 inches

Surface Finish:

32.0 microinches outside diameter

**Special Features:** 

Radius 0.010 in. Min, 0.030 in.Max located on bearing surface of head

Height:

Between 0.040 inches and 0.060 inches

Material:

Steel comp 440c

**Material Specification:** 

Qq-s-763 federal specification single material response

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Ems 250 ty2 cla scm 72599 mfr ref single treatment response

Style Designator:

Straight

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5315-00-949-9064

Headed Straight Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0