

View Online at <https://aerobasegroup.com/nsn/5315-00-949-9064>

Head Style:

Pan no. 2 (r1 not required in item description)

Chamfer Length:

Between 0.020 inches and 0.030 inches

Diameter:

Between 0.156 inches and 0.157 inches

Under Head Length:

Between 0.645 inches and 0.655 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.061 inches and 0.065 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.100 inches and 0.120 inches

Features Provided:

Casehardened

Hardness Rating:

52.0 rockwell c and 56.0 rockwell c

Pin Chamfer Angle:

Between 43.0 degrees and 47.0 degrees

Pin Head Diameter:

Between 0.300 inches and 0.320 inches

Surface Finish:

32.0 microinches outside diameter

Special Features:

Radius 0.010 in. Min, 0.030 in. Max located on bearing surface of head

Height:

Between 0.040 inches and 0.060 inches

Material:

Steel comp 440c

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ems 250 ty2 cla scm 72599 mfr ref single treatment response

Style Designator:

Straight

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0