## NSN 5315-00-949-9111

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-949-9111 **Shank Diameter:** Between 0.9970 inches and 0.9985 inches **Detent Quantity:** 2 **Actuation Method:** Push button **End Application:** Ws: missile, minuteman lgm-30; aircraft, harrier av-8b; aircraft, b-2 bomber (atb) **Grip Length:** Between 5.100 inches and 5.120 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c spindle **Shear Strength:** 147000 double pound **Shoulder To Head End Distance:** 2.170 inches Pin Center To Handle End Distance: 2.900 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** Between 0.860 inches and 0.890 inches Material: Steel comp 630 spindle or steel comp 632 spindle **Material Specification:** Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle **Surface Treatment:** Passivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spindle **Style Designator:** L handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

**Fiig:** A212a0

No