

View Online at <https://aerobasegroup.com/nsn/5315-00-952-2617>

**Head Diameter:**

Between 0.360 inches and 0.450 inches

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

Multiple launch rocket system (mlrs); tactical aircrew combat training sys (tacts); filter unit, gas particulate; m56; missile, minuteman lgm-30; aircraft, t-37; over the horizon back scanner (oth-b) program (an/fps-118); collective protective equipment cbr, m10

**Grip Length:**

Between 1.300 inches and 1.320 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

0.935 inches

**Pin Attachment Type:**

Hook

**Detent To Tapered End Distance:**

Between 0.360 inches and 0.410 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0