

View Online at <https://aerobasegroup.com/nsn/5315-00-952-2617>

Head Diameter:

Between 0.360 inches and 0.450 inches

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

Multiple launch rocket system (mlrs); tactical aircrew combat training sys (tacts); filter unit, gas particulate; m56; missile, minuteman lgm-30; aircraft, t-37; over the horizon back scanner (oth-b) program (an/fps-118); collective protective equipment cbr, m10

Grip Length:

Between 1.300 inches and 1.320 inches

Actuation Type:

Pull and push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

0.935 inches

Pin Attachment Type:

Hook

Detent To Tapered End Distance:

Between 0.360 inches and 0.410 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0