

NSN 5315-00-957-6521 Quick Release Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-00-957-6521 **Head Diameter:** 0.750 inches **Shank Diameter:** Between 0.3720 inches and 0.3745 inches **Ring Handle Diameter:** 1.240 inches **Actuation Method:** Push button **Grip Length:** Between 2.300 inches and 2.320 inches **Actuation Type:** Pull and push **Features Provided:** Drive out feature Hardness Rating: 54.0 rockwell c detent and 64.0 rockwell c detent **Shear Strength:** 18400 double pounds per square inch

Shoulder To Head End Distance:

1.730 inches

Pin Attachment Type:

Hook

Detent To Tapered End Distance:

0.510 inches

Special Features:

Steel attaching hook with cadmium surface treatment specification qq-p-416, type 2, cl 3

Material:

Steel spring

Material Specification:

Qq-w-470 federal specification single material response spring

Surface Treatment:

Passivate detent

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response shank

Style Designator:

Ring handle

Specification Data:

80205-nas1356 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5315-00-957-6521

Quick Release Pin - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.