# NSN 5315-00-958-1323

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-958-1323

#### Head Diameter:

0.750 inches

#### Shank Diameter:

Between 0.1870 inches and 0.1895 inches

### Ring Handle Diameter:

1.220 inches

#### **Detent Quantity:**

2

#### **Actuation Method:**

Push button

Grip Length:

Between 0.400 inches and 0.420 inches

#### Actuation Type:

Pull and push

#### **Features Provided:**

Drive out feature

### Hardness Rating:

54.0 rockwell c detent and 64.0 rockwell c detent

#### Shoulder To Head End Distance:

1.730 inches

#### Pin Attachment Type:

Hook or ring

#### Detent To Tapered End Distance:

0.410 inches

Material:

Steel comp 4130 spindle

#### **Material Specification:**

Mil-s-6758 military specification single material response spindle

#### Surface Treatment:

Cadmium spindle and chromate spindle

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

#### Style Designator:

Ring handle

#### **Specification Data:**

80205-nas1353 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

No

# NSN 5315-00-958-1323

Quick Release Pin - Page 2 of 2

Fiig: A212a0 Mil-std (military Standard): Mil-s-6758 spec.

