

View Online at <https://aerobasegroup.com/nsn/5315-00-962-6119>

**First End Style:**

Chamfered

**Second End Style:**

Round

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.188 inches and 0.218 inches

**Shank Length:**

Between 0.220 inches and 0.280 inches

**Shoulder Diameter:**

Between 0.185 inches and 0.187 inches

**Shank Diameter:**

Between 0.097 inches and 0.127 inches

**Overall Length:**

Between 1.205 inches and 1.235 inches

**Undercut Diameter:**

Between 0.065 inches and 0.075 inches

**Undercut Width:**

Between 0.032 inches and 0.062 inches

**Second Undercut Width:**

Between 0.032 inches and 0.062 inches

**Second Undercut Diameter:**

Between 0.065 inches and 0.075 inches

**First End Taper Length:**

0.030 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.112 inches

**Second Shank Diameter:**

Between 0.097 inches and 0.127 inches

**First End Location:**

Shank end

**First End Taper Angle:**

Between 44.5 degrees and 45.5 degrees

**Surface Finish:**

63.0 microinches outside diameter

**Second End Outer Radius:**

0.093 inches

**Second Shank Length:**

Between 0.220 inches and 0.280 inches

**Material:**

Steel comp 303se

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Undercut

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0