## NSN 5315-00-965-6506

First End Style:

Second End Style:

**Thread Class:** 

Right-hand **Thread Length:**0.410 inches

**Thread Direction:** 

Chamfered

Radius

2a

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-965-6506

Shan	k Length:
0.570	) inches
Shou	ılder Diameter:
Betwe	een 0.247 inches and 0.249 inches
Shan	k Diameter:
Betwe	een 0.1571 inches and 0.1640 inches
Over	all Length:
Betwe	een 2.150 inches and 2.160 inches
Hole	Arrangement Style:
One e	end drilled
First	Hole Diameter:
Betwe	een 0.035 inches and 0.045 inches
Dista	nnce From Centerline Of Hole To End Of Pin:
0.245	5 inches
Seco	ond End Corner Radius:
0.030	) inches
First	End Taper Length:
Betwe	een 0.080 inches and 0.110 inches
Seco	and End Relationship With First End:
Not ic	dentical
Hard	ness Rating:
42.0	rockwell c and 50.0 rockwell c
Threa	ad Size:
0.164	1 inches
First	End Location:
Threa	aded end
First	End Taper Angle:
Betwe	een 40.0 degrees and 50.0 degrees
Mate	rial:
Stain	less steel
Mate	rial Specification:
Ams	5616 assn standard single material response

## NSN 5315-00-965-6506

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:	
Chromium	
Surface Treatment Specification:	
Ams 2406 assn standard single treatment response	
Style Designator:	
Shoulder	
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

A212a0