## NSN 5315-00-966-7087

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-966-7087 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.500 inches **Shank Length:** Between 0.589 inches and 0.599 inches **Shoulder Width Across Flats:** 0.750 inches **Shank Diameter:** 0.250 inches **Overall Length:** Between 1.245 inches and 1.255 inches First End Taper Length: 0.032 inches **Second End Taper Length:** 0.500 inches Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches **Second Shank Diameter:** Between 0.303 inches and 0.307 inches **First End Location:** Threaded end First End Taper Angle: 45.0 degrees **Second End Taper Angle:** 5.0 degrees **Second Shank Length:** Between 0.526 inches and 0.536 inches Material: Steel comp 303 **Material Specification:** Qq-s-764, cond a federal specification single material response

Surface Treatment:

**Passivate** 

## NSN 5315-00-966-7087

Headless Shoulder Pin - Page 2 of 2



Mil-f-14072, e300 military specification single treatment response

**Style Designator:** 

Shoulder

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-f-14072 spec.