

View Online at <https://aerobasegroup.com/nsn/5315-00-968-0554>

**Head Diameter:**

Between 0.360 inches and 0.390 inches

**Shank Diameter:**

Between 0.2455 inches and 0.2470 inches

**Ring Handle Diameter:**

Between 0.997 inches and 1.003 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 1.750 inches and 1.753 inches

**Actuation Type:**

Push

**Shoulder To Head End Distance:**

0.656 inches

**Detent To Tapered End Distance:**

0.344 inches

**Special Features:**

Shank flatten to 0.225 in. W 0.120 from head 1.250 in. Lg

**Material:**

Steel comp 4340 spindle or steel comp 4140 spindle or steel comp 4130 spindle

**Material Specification:**

Mil-t-6736 military specification 1st material response shank or mil-t-6735 military specification 2nd material response shank or mil-t-6732 military specification 3rd material response shank

**Surface Treatment:**

Cadmium spindle

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5000 spec.