NSN 5315-00-969-4332

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-969-4332

Head Diameter:

Between 0.310 inches and 0.530 inches

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Ring Handle Diameter:

1.060 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.700 inches and 1.720 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c

Shear Strength:

9200 double pounds per square inch

Shoulder To Head End Distance:

0.780 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.260 inches and 0.290 inches

Special Features:

Cres attaching hook or ring qq-w-423 comp 302, passivated qq-p-35

Material:

Steel comp 631 spring or steel comp 302 spring

Material Specification:

Qq-w-423 federal specification single material response ring

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5315-00-969-4332

Quick Release Pin - Page 2 of 2

Fiig: A212a0 Mil-std (military Standard):

Mil-w-52263 spec.

