

View Online at <https://aerobasegroup.com/nsn/5315-00-974-0786>

First End Style:

Chamfered

Head Style:

Flat

Diameter:

Between 0.373 inches and 0.374 inches

Effective Length:

Between 1.723 inches and 1.767 inches

Undercut Diameter:

Between 0.342 inches and 0.344 inches

Under Head Length:

Between 2.300 inches and 2.320 inches

Undercut Radius:

0.003 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.094 inches and 0.097 inches

Distance From Centerline Of Hole To End Of Pin:

Between 1.790 inches and 1.810 inches

First End Taper Length:

Between 0.080 inches and 0.100 inches

Grip Length:

Between 1.742 inches and 1.784 inches

First End Taper Angle:

45.0 degrees

Pin Head Diameter:

Between 0.620 inches and 0.640 inches

Surface Finish:

32.0 microinches shank end

Height:

Between 0.110 inches and 0.150 inches

Material:

Steel comp 303 or steel comp 303se

Material Specification:

Qq-s-764, cond a federal specification all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, e300 military specification single treatment response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-f-14072 spec.