NSN 5315-00-974-0786



| Headed Grooved Pin - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5315-00-974-0786 |
| First End Style: |
| Chamfered |
| Head Style: |
| Flat |
| Diameter: |
| Between 0.373 inches and 0.374 inches |
| Effective Length: |
| Between 1.723 inches and 1.767 inches |
| Undercut Diameter: |
| Between 0.342 inches and 0.344 inches |
| Under Head Length: |
| Between 2.300 inches and 2.320 inches |
| Undercut Radius: |
| 0.003 inches |
| Hole Arrangement Style: |
| One end drilled |
| First Hole Diameter: |
| Between 0.094 inches and 0.097 inches |
| Distance From Centerline Of Hole To End Of Pin: |
| Between 1.790 inches and 1.810 inches |
| First End Taper Length: |
| Between 0.080 inches and 0.100 inches |
| Grip Length: |
| Between 1.742 inches and 1.784 inches |
| First End Taper Angle: |
| 45.0 degrees |
| Pin Head Diameter: |
| Between 0.620 inches and 0.640 inches |
| Surface Finish: |

Surface Finish:

32.0 microinches shank end

Height:

Between 0.110 inches and 0.150 inches

Material:

Steel comp 303 or steel comp 303se

Material Specification:

Qq-s-764, cond a federal specification all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, e300 military specification single treatment response

Style Designator:

Groove

NSN 5315-00-974-0786

Headed Grooved Pin - Page 2 of 2



| Shelf | Life: |
|-------|-------|
| N/a | |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-f-14072 spec.