

View Online at <https://aerobasegroup.com/nsn/5315-00-974-5858>

**First End Style:**

Chamfered

**Second End Style:**

Square w/thru hole

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.036 inches and 0.046 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.070 inches

**Pinlength:**

0.580 inches

**Pindiameter:**

Between 0.0910 inches and 0.0920 inches

**First End Taper Length:**

Between 0.020 inches and 0.040 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

250.0 brinell standard

**First End Taper Angle:**

20.0 degrees

**Special Features:**

One end flatted 0.030 in. Thk, 0.140 in. Lg

**Material:**

Steel comp 303

**Material Specification:**

Qq-s-763, cl 303, cond a federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072, e300 military specification single treatment response

**Test Data Document:**

98230-0n088842 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-f-14072 spec.