NSN 5315-00-982-7331

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-982-7331 First End Style: Chamfered Second End Style: Counterbored w/o through hole **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.380 inches **Shank Length:** 2.250 inches **Shoulder Diameter:** 0.250 inches **Shank Diameter:** Between 0.186 inches and 0.190 inches **Overall Length:** 5.750 inches **Internal Drive Style:** Slot **Second End Counterbore Diameter:** Between 0.189 inches and 0.192 inches **Second End Counterbore Depth:** 0.880 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Not identical **Hardness Rating:** 28.0 rockwell c and 32.0 rockwell c **Thread Size:** 0.190 inches First End Location: Shank end First End Taper Angle: 45.0 degrees **Surface Finish:** 125.000 microinches Material: Steel comp 4130

Material Specification:

Mil-s-6758 cond a military specification single material response

NSN 5315-00-982-7331

Headless Shoulder Pin - Page 2 of 2

Mil-std (military Standard):

Mil-s-6758 spec.



Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0