

View Online at <https://aerobasegroup.com/nsn/5315-00-982-7331>

**First End Style:**

Chamfered

**Second End Style:**

Counterbored w/o through hole

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.380 inches

**Shank Length:**

2.250 inches

**Shoulder Diameter:**

0.250 inches

**Shank Diameter:**

Between 0.186 inches and 0.190 inches

**Overall Length:**

5.750 inches

**Internal Drive Style:**

Slot

**Second End Counterbore Diameter:**

Between 0.189 inches and 0.192 inches

**Second End Counterbore Depth:**

0.880 inches

**First End Taper Length:**

0.020 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

28.0 rockwell c and 32.0 rockwell c

**Thread Size:**

0.190 inches

**First End Location:**

Shank end

**First End Taper Angle:**

45.0 degrees

**Surface Finish:**

125.000 microinches

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 cond a military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.