NSN 5315-00-984-5184

Headless Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-984-5184

| Chamfered Hole Arrangement Style: One end drilled First Hole Diameter: Between 0.125 inches and 0.129 inches Distance From Centerline Of Hole To End Of Pin: Between 0.500 inches and 0.520 inches Pinlength: 3.880 inches Pindiameter: Between 0.4950 inches and 0.4970 inches First End Taper Length: |
|--|
| One end drilled First Hole Diameter: Between 0.125 inches and 0.129 inches Distance From Centerline Of Hole To End Of Pin: Between 0.500 inches and 0.520 inches Pinlength: 3.880 inches Pindiameter: Between 0.4950 inches and 0.4970 inches |
| First Hole Diameter: Between 0.125 inches and 0.129 inches Distance From Centerline Of Hole To End Of Pin: Between 0.500 inches and 0.520 inches Pinlength: 3.880 inches Pindiameter: Between 0.4950 inches and 0.4970 inches |
| Between 0.125 inches and 0.129 inches Distance From Centerline Of Hole To End Of Pin: Between 0.500 inches and 0.520 inches Pinlength: 3.880 inches Pindiameter: Between 0.4950 inches and 0.4970 inches |
| Distance From Centerline Of Hole To End Of Pin: Between 0.500 inches and 0.520 inches Pinlength: 3.880 inches Pindiameter: Between 0.4950 inches and 0.4970 inches |
| Between 0.500 inches and 0.520 inches Pinlength: 3.880 inches Pindiameter: Between 0.4950 inches and 0.4970 inches |
| Pinlength:3.880 inchesPindiameter:Between 0.4950 inches and 0.4970 inches |
| 3.880 inches Pindiameter: Between 0.4950 inches and 0.4970 inches |
| Pindiameter: Between 0.4950 inches and 0.4970 inches |
| Between 0.4950 inches and 0.4970 inches |
| |
| First End Taper Length: |
| |
| 0.060 inches |
| Features Provided: |
| Casehardened |
| Second End Relationship With First End: |
| Identical |
| Hardness Rating: |
| 88.0 rockwell superficial 15-n and 91.0 rockwell superficial 15-n |
| First End Taper Angle: |
| 45.0 degrees |
| Surface Finish: |
| 63.0 microinches outside diameter |
| Material: |
| Steel comp 1016 or steel comp 1018 |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |
| |
| |