

View Online at <https://aerobasegroup.com/nsn/5315-00-989-0821>

First End Style:

Chamfered

Hole Arrangement Style:

Drilled through center

First Hole Diameter:

Between 0.0785 inches and 0.0788 inches

Pinlength:

Between 2.113 inches and 2.118 inches

Pindiameter:

Between 0.6230 inches and 0.6240 inches

First End Taper Length:

0.020 inches

Second End Relationship With First End:

Identical

Hardness Rating:

32.0 rockwell c and 36.0 rockwell c

First End Taper Angle:

45.0 degrees

Surface Finish:

16.0 microinches shank end

Material:

Steel comp e4340 or steel comp 4340

Material Specification:

Mil-s-5000 military specification all material responses

Surface Treatment:

Phosphate zinc

Surface Treatment Specification:

Mil-c-16232, ty2 military specification single treatment response

Test Data Document:

81343-mil-i-6848 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5000 spec.