## NSN 5315-00-990-2890



Headed Straight Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-00-990-2890 **Head Style:** Pan no. 2 (r1 not required in item description) **Chamfer Length:** 0.062 inches Diameter: Between 0.184 inches and 0.186 inches **Under Head Length:** Between 1.772 inches and 1.792 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.066 inches and 0.086 inches Distance From Centerline Of Hole To End Of Pin: 0.088 inches **Hardness Rating:** 26.5 rockwell c and 32.0 rockwell c Pin Chamfer Angle: Between 14.5 degrees and 15.5 degrees **Shear Strength:** 4140 double pound Pin Head Diameter: Between 0.296 inches and 0.328 inches **Special Features:** Shank end may have either a chamfer or radius at the option of the vendor Height: Between 0.030 inches and 0.062 inches Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630

**Material Specification:** 

Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification 3rd material response

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2 cl 2 federal specification single treatment response

**Style Designator:** 

Straight

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

## NSN 5315-00-990-2890

Headed Straight Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.