

View Online at <https://aerobasegroup.com/nsn/5315-00-996-7515>

**First End Style:**

Chamfered

**Head Style:**

Flat

**Under Head Length:**

Between 1.635 inches and 1.655 inches

**First Step Diameter:**

Between 0.371 inches and 0.373 inches

**First Step Length:**

Between 0.725 inches and 0.756 inches

**Second Step Diameter:**

Between 0.238 inches and 0.248 inches

**Second Step Length:**

Between 0.890 inches and 0.910 inches

**First End Taper Length:**

Between 0.010 inches and 0.050 inches

**First End Taper Angle:**

Between 40.0 degrees and 50.0 degrees

**Pin Head Diameter:**

Between 0.496 inches and 0.498 inches

**Special Features:**

Undercut located 0.135 in. Min, 0.175 in. Maximum from top of head, 0.240 in. Min, 0.311 in. Maximum lg, 0.238 in. Min, 0.248 in. Maximum od, extended washer located under head 0.540 in. Min, 0.560 in. Maximum od

**Height:**

0.150 inches

**Material:**

Steel

**Material Specification:**

Mil-s-5000, cond f military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5000 spec.