

View Online at <https://aerobasegroup.com/nsn/5315-00-996-7515>

First End Style:

Chamfered

Head Style:

Flat

Under Head Length:

Between 1.635 inches and 1.655 inches

First Step Diameter:

Between 0.371 inches and 0.373 inches

First Step Length:

Between 0.725 inches and 0.756 inches

Second Step Diameter:

Between 0.238 inches and 0.248 inches

Second Step Length:

Between 0.890 inches and 0.910 inches

First End Taper Length:

Between 0.010 inches and 0.050 inches

First End Taper Angle:

Between 40.0 degrees and 50.0 degrees

Pin Head Diameter:

Between 0.496 inches and 0.498 inches

Special Features:

Undercut located 0.135 in. Min, 0.175 in. Maximum from top of head, 0.240 in. Min, 0.311 in. Maximum lg, 0.238 in. Min, 0.248 in. Maximum od, extended washer located under head 0.540 in. Min, 0.560 in. Maximum od

Height:

0.150 inches

Material:

Steel

Material Specification:

Mil-s-5000, cond f military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5000 spec.