

View Online at <https://aerobasegroup.com/nsn/5315-00-998-1317>

First End Style:

Square

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.328 inches

Shoulder Diameter:

0.218 inches

Overall Length:

1.125 inches

First Step Diameter:

0.375 inches

First Step Length:

0.328 inches

Second Step Diameter:

Between 0.263 inches and 0.264 inches

Second Step Length:

0.406 inches

Third Step Diameter:

Between 0.152 inches and 0.153 inches

Third Step Length:

Between 0.264 inches and 0.269 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.045 inches and 0.050 inches

Distance From Centerline Of Hole To End Of Pin:

0.065 inches

Second End Relationship With First End:

Identical

Hardness Rating:

39.0 rockwell c and 45.0 rockwell c

Thread Size:

0.375 inches

First End Location:

Both ends

Surface Finish:

32.0 microinches

Special Features:

Has 0.153 in. Dia, 0.154 in. W circular groove 0.328 in. From small end

Material:

Steel comp 410

Material Specification:

Ams 5612 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5002 spec.