## NSN 5315-00-998-8146

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-998-8146

Shank Diameter:
Between 0.4345 inches and 0.4360 inches
Detent Quantity:
2
Actuation Method:
Push button
End Application:
Support equipment, f-16 aircraft; aircraft, b-2 bomber (atb); aircraft, f-16; engine, aircraft, f110-ge-100/129 (f-16 c/d)
Grip Length:
Between 1.300 inches and 1.320 inches
Actuation Type:
Push
Hardness Rating:
40.0 rockwell c spindle
Shoulder To Head End Distance:
1.470 inches
Pin Center To Handle End Distance:
Between 1.555 inches and 1.640 inches
Pin Attachment Type:
Link or ring
Detent To Tapered End Distance:
Between 0.350 inches and 0.380 inches
Material:
Steel comp 630 spindle or steel comp 632 spindle
Material Specification:
Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle
Surface Treatment:
Passivate spindle
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response spindle
Style Designator:
L handle
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A212a0