## NSN 5315-01-006-5796

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-006-5796 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.276 inches and 0.286 inches Shank Length: 0.389 inches **Shoulder Width Across Flats:** Between 0.111 inches and 0.113 inches **Shank Diameter:** Between 0.091 inches and 0.095 inches **Overall Length:** Between 0.780 inches and 0.800 inches First End Taper Length: 0.061 inches **Second End Taper Length:** Any acceptable **Second End Relationship With First End:** Not identical **Thread Size:** 0.112 inches **First End Location:** Unthreaded end First End Taper Angle: 60.0 degrees First End Tip Radius: 0.016 inches **Second End Taper Angle:** Any acceptable **Special Features:** Guide pin attached at unthreaded end (smaller) end Material: Steel comp 303 or steel comp 303se **Material Specification:** Qq-s-764, cond a federal specification single material response **Surface Treatment:** 

**Passivate** 

## NSN 5315-01-006-5796

Headless Shoulder Pin - Page 2 of 2



## **Surface Treatment Specification:**

Qq-p-35, type 1, 2, or 3 federal specification single treatment response

**Style Designator:** 

Shoulder

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A212a0