## NSN 5315-01-007-1968

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-007-1968 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.370 inches **Shank Length:** 0.430 inches **Shoulder Width Across Flats:** 0.437 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Overall Length:** 1.058 inches First End Taper Length: 0.047 inches **Second End Taper Length:** 0.280 inches Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches **Second Shank Diameter:** Between 0.245 inches and 0.250 inches **First End Location:** Threaded end First End Taper Angle: 50.0 degrees **Second End Tip Radius:** 0.062 inches **Surface Finish:** 125.0 microinches **Second Shank Length:** 0.508 inches Material: Steel comp 4340

**Material Specification:** 

Mil-s-5000, cond d military specification single material response

## NSN 5315-01-007-1968

Headless Shoulder Pin - Page 2 of 2

Mil-s-5000 spec.



Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416a, type 2, class 3 federal specification single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0
Mil-std (military Standard):