NSN 5315-01-008-7098

No Fiig: A212a0



Quick Release Pin - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5315-01-008-7098 **Head Diameter:** Between 0.360 inches and 0.450 inches **Shank Diameter:** Between 0.2470 inches and 0.2485 inches **Ring Handle Diameter:** Between 1.080 inches and 1.275 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 0.500 inches and 0.520 inches **Actuation Type:** Pull and push **Features Provided:** Drive out feature **Shoulder To Head End Distance:** Between 0.935 inches and 1.100 inches Pin Attachment Type: Cable lanyard w/terminations **Detent To Tapered End Distance:** Between 0.360 inches and 0.410 inches Material: Steel comp 302 shank or steel comp 303 shank or steel comp 303se shank or steel comp 304 shank or steel comp 304 shank or steel comp 305 shank or steel comp 309 shank or steel comp 310 shank or steel comp 316 shank or steel comp 316 shank or steel comp 317 shank or steel comp 316 shank or steel comp 316 shank or steel comp 317 shank or steel comp 316 shank or steel comp 316 shank or steel comp 316 shank or steel comp 317 shank or steel comp 316 shank or steel comp 316 shank or steel comp 316 shank or steel comp 317 shank or steel comp 316 shank or steel comp 316 shank or steel comp 317 shank or steel comp 318 sh steel comp 321 shank or steel comp 347 shank **Surface Treatment:** Passivate shank **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response shank **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure: Demilitarization:**