

View Online at <https://aerobasegroup.com/nsn/5315-01-008-7100>

**Head Diameter:**

Between 0.640 inches and 0.755 inches

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 2.200 inches and 2.220 inches

**Actuation Type:**

Pull and push

**Features Provided:**

Drive out feature

**Shoulder To Head End Distance:**

Between 1.600 inches and 1.700 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

Between 0.540 inches and 0.590 inches

**Material:**

Steel comp 302 shank or steel comp 303 shank or steel comp 303se shank or steel comp 304l shank or steel comp 304 shank or steel comp 305 shank or steel comp 309 shank or steel comp 310 shank or steel comp 316 shank or steel comp 316l shank or steel comp 317 shank or steel comp 317 shank or steel comp 321 shank or steel comp 347 shank

**Surface Treatment:**

Passivate shank

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0