## NSN 5315-01-008-8254

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-008-8254 First End Style: Square **Head Style:** Bevel **Under Head Length:** Between 1.419 inches and 1.421 inches First Step Diameter: Between 0.372 inches and 0.374 inches First Step Length: Between 1.180 inches and 1.220 inches **Second Step Diameter:** Between 0.197 inches and 0.203 inches Second Step Length: Between 0.199 inches and 0.241 inches Hardness Rating: 33.0 rockwell c and 38.0 rockwell c Pin Head Diameter: Between 0.550 inches and 0.570 inches **Surface Finish:** 125.0 microinches **Special Features:** 0.078 in diameter hole located 0.110 in. From hole center to shank end Height: Between 0.250 inches and 0.330 inches Material: Steel comp 4140 or steel **Material Specification:** Qq-s-624 comp 4140 federal specification 1st material response or ams 6395 comp 4140 assn standard 2nd material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Mil-std-171 finish 5.3.1.2 or 5.3.2.2 military standard single treatment response **Style Designator:** Shoulder Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No **Fiig:** 

A212a0

## NSN 5315-01-008-8254

Headed Shoulder Pin - Page 2 of 2



Mil-std (military Standard):

Mil-std-171 spec.