NSN 5315-01-011-5589

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-011-5589

| First End Style: |
|---|
| Chamfered |
| |
| Second End Style: |
| Radius |
| Shank Length: |
| Between 0.213 inches and 0.223 inches |
| Shoulder Diameter: |
| Between 0.1876 inches and 0.1878 inches |
| Shank Diameter: |
| Between 0.1871 inches and 0.1874 inches |
| Overall Length: |
| Between 0.495 inches and 0.505 inches |
| Second End Corner Radius: |
| Between 0.016 inches and 0.047 inches |
| First End Taper Length: |
| Between 0.057 inches and 0.067 inches |
| Second End Relationship With First End: |
| Not identical |
| Hardness Rating: |
| 36.0 rockwell c and 42.0 rockwell c |
| Shear Strength: |
| 4000 double pounds per square inch |
| First End Location: |
| Shoulder end |
| First End Taper Angle: |
| Between 4.0 degrees and 16.0 degrees |
| Surface Finish: |
| 16.0 microinches shoulder end |
| Material: |
| Steel comp 410 or steel comp 416 |
| Material Specification: |
| Qq-s-763 federal specification all material responses |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Ga3023, fscm 01714 mfr ref single treatment response |
| Style Designator: |
| Shoulder |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5315-01-011-5589

Headless Shoulder Pin - Page 2 of 2

Demilitarization:

No

Fiig:

A212a0

