## NSN 5315-01-013-3396

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-013-3396

First End Style:
Chamfered
Second End Style:
Chamfered
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.420 inches
Shank Length:
0.625 inches
Shoulder Width Across Flats:
0.625 inches
Shank Diameter:
Between 0.381 inches and 0.382 inches
Overall Length:
1.743 inches
First End Taper Length:
0.031 inches
Second End Taper Length:
0.181 inches
0.181 inches  Second End Relationship With First End:
Second End Relationship With First End:
Second End Relationship With First End: Not identical
Second End Relationship With First End: Not identical Hardness Rating:
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c Thread Size:
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c Thread Size: 0.375 inches
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c Thread Size: 0.375 inches Second Shank Diameter:
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c Thread Size: 0.375 inches Second Shank Diameter: Between 0.381 inches and 0.382 inches
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c Thread Size: 0.375 inches Second Shank Diameter: Between 0.381 inches and 0.382 inches First End Location:
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c Thread Size: 0.375 inches Second Shank Diameter: Between 0.381 inches and 0.382 inches First End Location: Both ends
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c Thread Size: 0.375 inches Second Shank Diameter: Between 0.381 inches and 0.382 inches First End Location: Both ends First End Taper Angle:
Second End Relationship With First End:  Not identical  Hardness Rating:  40.0 rockwell c and 47.0 rockwell c  Thread Size:  0.375 inches  Second Shank Diameter:  Between 0.381 inches and 0.382 inches  First End Location:  Both ends  First End Taper Angle:  20.0 degrees
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c Thread Size: 0.375 inches Second Shank Diameter: Between 0.381 inches and 0.382 inches First End Location: Both ends First End Taper Angle: 20.0 degrees Surface Finish:
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c Thread Size: 0.375 inches Second Shank Diameter: Between 0.381 inches and 0.382 inches First End Location: Both ends First End Taper Angle: 20.0 degrees Surface Finish: 63.000 microinches
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c Thread Size: 0.375 inches Second Shank Diameter: Between 0.381 inches and 0.382 inches First End Location: Both ends First End Taper Angle: 20.0 degrees Surface Finish: 63.000 microinches Second End Taper Angle:
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c Thread Size: 0.375 inches Second Shank Diameter: Between 0.381 inches and 0.382 inches First End Location: Both ends First End Taper Angle: 20.0 degrees Surface Finish: 63.000 microinches Second End Taper Angle: 45.0 degrees
Second End Relationship With First End: Not identical Hardness Rating: 40.0 rockwell c and 47.0 rockwell c Thread Size: 0.375 inches Second Shank Diameter: Between 0.381 inches and 0.382 inches First End Location: Both ends First End Taper Angle: 20.0 degrees Surface Finish: 63.000 microinches Second End Taper Angle: 45.0 degrees Second Shank Length:

## NSN 5315-01-013-3396

Headless Shoulder Pin - Page 2 of 2



Material Specification:
Ams 5643 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A212a0