## NSN 5315-01-013-7196

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-013-7196 First End Style: Chamfered **Second End Style:** Radius **Shank Length:** Between 0.245 inches and 0.255 inches Shoulder Diameter: Between 0.1251 inches and 0.1253 inches **Shank Diameter:** Between 0.1246 inches and 0.1249 inches **Overall Length:** Between 0.495 inches and 0.505 inches **Second End Corner Radius:** Between 0.016 inches and 0.047 inches First End Taper Length: Between 0.120 inches and 0.130 inches Second End Relationship With First End: Not identical **Hardness Rating:** 36.0 rockwell c and 42.0 rockwell c **Shear Strength:** 1800 double pounds per square inch **First End Location:** Shoulder end First End Taper Angle: Between 4.0 degrees and 16.0 degrees Surface Finish: 16.0 microinches shoulder end Material: Steel comp 410 or steel comp 416 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Ga3032, fscm 01714 mfr ref single treatment response **Style Designator:** Shoulder Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5315-01-013-7196

Headless Shoulder Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0