## NSN 5315-01-014-9581

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-014-9581 **Head Diameter:** Between 0.360 inches and 0.430 inches **Shank Diameter:** Between 0.2331 inches and 0.2346 inches **Ring Handle Diameter:** 1.125 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** 1.5748 inches **Actuation Type:** Pull and push **Hardness Rating:** 58.0 rockwell c and 62.0 rockwell c **Shear Strength:** 7118 double pounds per square inch **Shoulder To Head End Distance:** 1.945 inches Pin Attachment Type: Ring **Detent To Tapered End Distance:** Between 0.380 inches and 0.410 inches Material: Steel spring **Material Specification:** Qq-w-470 federal specification single material response spring **Surface Treatment:** Passivate handle **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response spring **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A212a0

## NSN 5315-01-014-9581

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.