NSN 5315-01-021-0056

Headless Shoulder Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-021-0056

First End Style:ChamferedShank Length:3.906 inchesShoulder Diameter:1.500 inchesShank Diameter:Between 0.994 inches and 0.996 inchesOverall Length:6.344 inchesFirst End Taper Length:0.062 inchesSecond End Relationship With First End:IdenticalSecond Shank Diameter:Any acceptableFirst End Location:Both endsFirst End Taper Angle:45.0 degreesSurface Finish:
Shank Length:3.906 inchesShoulder Diameter:1.500 inchesShank Diameter:Between 0.994 inches and 0.996 inchesOverall Length:6.344 inchesFirst End Taper Length:0.062 inchesSecond End Relationship With First End:IdenticalSecond Shank Diameter:Any acceptableFirst End Location:Both endsFirst End Taper Angle:45.0 degrees
3.906 inchesShoulder Diameter:1.500 inchesShank Diameter:Between 0.994 inches and 0.996 inchesOverall Length:6.344 inchesFirst End Taper Length:0.062 inchesSecond End Relationship With First End:IdenticalSecond Shank Diameter:Any acceptableFirst End Location:Both endsFirst End Taper Angle:45.0 degrees
Shoulder Diameter:1.500 inchesShank Diameter:Between 0.994 inches and 0.996 inchesOverall Length:6.344 inchesFirst End Taper Length:0.062 inchesSecond End Relationship With First End:IdenticalSecond Shank Diameter:Any acceptableFirst End Location:Both endsFirst End Taper Angle:45.0 degrees
1.500 inches Shank Diameter: Between 0.994 inches and 0.996 inches Overall Length: 6.344 inches First End Taper Length: 0.062 inches Second End Relationship With First End: Identical Second Shank Diameter: Any acceptable First End Location: Both ends First End Taper Angle: 45.0 degrees
Shank Diameter:Between 0.994 inches and 0.996 inchesDverall Length:6.344 inchesFirst End Taper Length:0.062 inchesSecond End Relationship With First End:IdenticalSecond Shank Diameter:Any acceptableFirst End Location:Both endsFirst End Taper Angle:45.0 degrees
Between 0.994 inches and 0.996 inchesOverall Length:6.344 inchesFirst End Taper Length:0.062 inchesBecond End Relationship With First End:IdenticalSecond Shank Diameter:Any acceptableFirst End Location:Both endsFirst End Taper Angle:45.0 degrees
Overall Length:6.344 inchesFirst End Taper Length:0.062 inchesSecond End Relationship With First End:IdenticalSecond Shank Diameter:Any acceptableFirst End Location:Both endsFirst End Taper Angle:45.0 degrees
6.344 inches First End Taper Length: 0.062 inches Second End Relationship With First End: Identical Second Shank Diameter: Any acceptable First End Location: Both ends First End Taper Angle: 45.0 degrees
First End Taper Length:0.062 inchesSecond End Relationship With First End:IdenticalSecond Shank Diameter:Any acceptableFirst End Location:Both endsFirst End Taper Angle:45.0 degrees
0.062 inches Second End Relationship With First End: Identical Second Shank Diameter: Any acceptable First End Location: Both ends First End Taper Angle: 45.0 degrees
Second End Relationship With First End:IdenticalSecond Shank Diameter:Any acceptableFirst End Location:Both endsFirst End Taper Angle:45.0 degrees
Identical Second Shank Diameter: Any acceptable First End Location: Both ends First End Taper Angle: 45.0 degrees
Second Shank Diameter: Any acceptable First End Location: Both ends First End Taper Angle: 45.0 degrees
Any acceptable First End Location: Both ends First End Taper Angle: 45.0 degrees
First End Location: Both ends First End Taper Angle: 45.0 degrees
First End Taper Angle: 45.0 degrees
45.0 degrees
-
Surface Finish:
63.0 microinches shoulder end
Second Shank Length:
Any acceptable
Special Features:
Undercut dim. 1.781 in. From end, 0.812 in. Dia, 0.344 in. Width, and grip dim. Above shoulder 0.724 in. Dia, 1.250 in. Lg
Material:
Steel comp 4340
Material Specification:
Qq-s-624 federal specification single material response
Style Designator:
Shoulder
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0