

View Online at <https://aerobasegroup.com/nsn/5315-01-022-8272>

**Head Diameter:**

Between 0.485 inches and 0.515 inches

**Shank Diameter:**

Between 0.3700 inches and 0.3730 inches

**Ring Handle Diameter:**

1.187 inches

**Detent Quantity:**

2

**Lanyard Length:**

Between 13.500 inches and 14.500 inches

**Grip Length:**

Between 6.500 inches and 6.520 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

58.0 rockwell c detent and 62.0 rockwell c detent

**Shoulder To Head End Distance:**

0.562 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

0.390 inches

**Material:**

Steel comp 302 shank or steel comp 304 shank or steel comp 304l shank or steel comp 305 shank or steel comp 309 shank or steel comp 310 shank or steel comp 316 shank or steel comp 316l shank or steel comp 317 shank or steel comp 321 shank or steel comp 347 shank

**Material Specification:**

Qq-s-763 federal specification all material responses shank

**Surface Treatment:**

Passivate shank

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0