NSN 5315-01-029-7640

Headless Shoulder Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-029-7640

First End Style:
Pointed
Shank Length:
0.448 inches
Shoulder Diameter:
0.125 inches
Shank Diameter:
Between 0.068 inches and 0.072 inches
Overall Length:
0.573 inches
Second End Relationship With First End:
Identical
Second Shank Diameter:
Between 0.078 inches and 0.080 inches
First End Location:
Large end
First End Taper Angle:
30.0 degrees
Second Shank Length:
0.105 inches
Material:
Steel comp 303
Material Specification:
Material Specification: Astm a582 type 303 assn standard single material response
-
Astm a582 type 303 assn standard single material response
Astm a582 type 303 assn standard single material response Surface Treatment:
Astm a582 type 303 assn standard single material response Surface Treatment: Passivate
Astm a582 type 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Astm a582 type 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: 580-0025-000 fscm 13499 mfr ref single treatment response
Astm a582 type 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: 580-0025-000 fscm 13499 mfr ref single treatment response Style Designator:
Astm a582 type 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: 580-0025-000 fscm 13499 mfr ref single treatment response Style Designator: Shoulder
Astm a582 type 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: 580-0025-000 fscm 13499 mfr ref single treatment response Style Designator: Shoulder Shelf Life:
Astm a582 type 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: 580-0025-000 fscm 13499 mfr ref single treatment response Style Designator: Shoulder Shelf Life: N/a
Astm a582 type 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: 580-0025-000 fscm 13499 mfr ref single treatment response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure:
Astm a582 type 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: 580-0025-000 fscm 13499 mfr ref single treatment response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure:
Astm a582 type 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: 580-0025-000 fscm 13499 mfr ref single treatment response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization:
Astm a582 type 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: 580-0025-000 fscm 13499 mfr ref single treatment response Style Designator: Shoulder Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No
Astm a582 type 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: 580-0025-000 fscm 13499 mfr ref single treatment response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: