

View Online at <https://aerobasegroup.com/nsn/5315-01-030-0580>

**First End Style:**

Chamfered

**Head Style:**

Knurled no. 1

**Under Head Length:**

3.186 inches

**First Step Diameter:**

Between 0.811 inches and 0.812 inches

**First Step Length:**

0.468 inches

**Second Step Diameter:**

Between 0.5605 inches and 0.5615 inches

**Second Step Length:**

2.718 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

0.109 inches

**Distance From Centerline Of Hole To End Of Pin:**

1.106 inches

**First End Taper Length:**

0.050 inches

**Shear Strength:**

140000 single pounds per square inch

**First End Taper Angle:**

45.0 degrees

**Pin Head Diameter:**

1.125 inches

**Surface Finish:**

32.0 microinches

**Height:**

0.187 inches

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Phosphate zinc

**Surface Treatment Specification:**

D0d-p-16232 type z class 1 national specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.