NSN 5315-01-032-3730



Headless Shoulder Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-01-032-3730 First End Style: Chamfered **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.120 inches and 0.140 inches **Shank Length:** Between 0.530 inches and 0.560 inches **Shoulder Diameter:** Between 0.245 inches and 0.250 inches **Shank Diameter:** Between 0.1895 inches and 0.1900 inches **Overall Length:** Between 0.890 inches and 0.910 inches **Internal Drive Style:** Slot **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.044 inches and 0.051 inches Distance From Centerline Of Hole To End Of Pin: Between 0.050 inches and 0.060 inches First End Taper Length: Between 0.020 inches and 0.040 inches Second End Relationship With First End: Identical **Hardness Rating:** 35.0 rockwell c **Thread Size:** 0.190 inches First End Location:

Both ends First End Taper Angle: 45.0 degrees Surface Finish: 32.0 microinches large shank

Material:

Steel comp 416f

Material Specification:

Ams 5610 assn standard single material response

NSN 5315-01-032-3730

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Astm a380 assn standard single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0