## NSN 5315-01-033-1277

Eccentric Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-033-1277

Width Between Flats:
0.187 inches
Overall Length:
2.344 inches
Offset Distance Between Geometric Center Of Head And Centerline Of Shank/shoulder:
0.062 inches
First Step Diameter:
0.875 inches
Third Step Diameter:
Between 0.245 inches and 0.250 inches
Third Step Length:
0.641 inches
Internal Drive Style:
Socket
Shear Strength:
3870 single pound
Special Features:
One end threaded 0.375-24unf-3a; eccentric hex bushing and round concentric bushing and locknut included
· · · ·
Material:
Material: Steel comp 303
Steel comp 303
Steel comp 303 Surface Treatment:
Steel comp 303  Surface Treatment:  Passivate
Steel comp 303  Surface Treatment:  Passivate  Style Designator:
Steel comp 303  Surface Treatment:  Passivate  Style Designator:  Eccentric
Steel comp 303  Surface Treatment:  Passivate  Style Designator:  Eccentric  Shelf Life:
Steel comp 303  Surface Treatment:  Passivate  Style Designator:  Eccentric  Shelf Life:  N/a
Steel comp 303  Surface Treatment:  Passivate  Style Designator:  Eccentric  Shelf Life:  N/a
Steel comp 303  Surface Treatment:  Passivate  Style Designator:  Eccentric  Shelf Life:  N/a  Unit Of Measure:
Steel comp 303  Surface Treatment:  Passivate  Style Designator:  Eccentric  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: